LOBADUR[™]≈ WS 2K DUO



Glossy

Water-based 2-component polyurethane finish for wooden floors. For extremely heavy wear.

Emissions

Loba GmbH & G. KG Emissiongsprüfter Bauprodakt nob Directione 2/157.10-2	Approval number Z-157.10-2	According to DIBt (German institute for building technology)
CH ^{4510N C(410} M1 ² 492/YW ON ^{UCS}	Harmless according to expert evaluation of VOC, ingredients and odour	According to RTS (Building Information Foundation Finland)

Technical evaluation

2004/42/CE	EU limit value for this product (cat. A/j): 140 g/l (2010). , This product contains max. 92 g/l VOC(mixture with hardener).
GISCODE	W3/DD+ (Water seal with isocyanate-containing hardener, solvent content up to 15%, N-methylpyrrolidone free)

Glossar

DIBt

For reasons of health protection, the German Institute for Building Technology (DIBt) requires a general building supervisory approval for all building products used for the treatment and bonding of parquet on site. Certified building materials are marked with the Ü symbol. This obligation to obtain approval has been in force in Germany since 1 January 2011. In order to obtain approval, compliance with emission limits must be proven and the formulations must be disclosed to the DIBt. www.dibt.de

М1

The M 1 classification is part of the voluntary Finnish indoor climate classification system. It is published by the Finnish Association for Indoor Air and Climate (FiSIAQ).

2004/42/CE

The "Decopaint-Directive" is a limitation of volatile organic compounds (VOC)* proclaimed by the EU due to the use of organic solvents in certain paints and varnishes.

GISCODE

The term GISCODE stands for Hazardous Substance Information System Code and was developed by the BG Bau (Employer's Liability Insurance Association for the Construction Industry). It is a labelling system in which products with comparable health hazards are grouped together in product groups. The coding consists of a letter/ number combination that uniquely assigns the product to a product group. To obtain specific product information, a product group can be selected on the GISBAU website (= Hazardous Substance Information System of the BG Bau) and detailed hazardous substance information can be found in the appropriate table.

Notes

Disclaimer

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and relate to Spezial conditions. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice by speaking to the LOBA application engineering department. Observe the floor covering manufacturer's recommendations and the provisions of the current standards. Our liabilities and responsibilities are exclusively in accordance with our Terms and Conditions and are not extended by this information or by our advice. The publishing of a new technical data sheet automatically invalidates the earlier version.