TECHNICAL INFORMATION DeckCleaner





IEW

From nature - for nature! Powerful herbal based cleaning for your outdoor area

Maintenance cleaner for outdoor areas. LOBACARE DeckCleaner cleans quickly and thoroughly on a vegetable basis. It removes even stubborn dirt gently and is biodegradable.

- · Can be used for maintenance and intensive cleaning
- Very productive
- Suitable for oiled and finished wood and WPC

Range of use:

Suitable for cleaning WPC, oiled and finished wood.

Technical Data

Artno. 10731	2,5 I 6 144
рН	9.6
Contents	5 - 15% soap
Storage and transportation	36 months of storage stability. No hazardous material according to ADR. Store and transport between +5 to +25°C. Protect from frost.
GISCODE	GU70

Application

- Remove any loose dirt and dust in advance using a vacuum, brush or mop.
- Observe general and, if necessary, product-specific occupational health and safety regulations. Further information can be found in the GISCODE-related operating instructions which are available under <u>www.wingis-online.de</u>.
- Shake the contents well.

Thinner

Water.

Application tool/application rate

LOBATOOL Mop or Scrubber / add approx. 50 - 250 ml to 10 l water.

OBA GmbH & Co. KG | Leonberger Str. 56-62 | 71254 Ditzingen | Germany on: +49 7156 357-0 | Fax: +49 7156 357-211 | E-Mail: service@loba.de | www.loba.de

TECHNICAL INFORMATION DeckCleaner



Application

Application:

For regular cleaning and before applying DeckRefresh and WPC Refresh. Depending on the degree of soiling, mix approx. 50 - 250 ml of DeckCleaner with 10l of water. Apply cleaning solution to the surface and remove after a short exposure time with the LOBATOOL mop. In case of grooved terrace decks or heavy soiling, treat the surface with a scrubbing brush. If necessary, repeat the cleaning process. Then rinse off any cleaning agent residues with clear water. In case of high application concentration, a slight leaching may occur on oiled surfaces. In this case, we recommend a subsequent application of WPC Refresh on these surfaces after drying overnight to restore the impregnation. High application concentrations can lead to leaching of the oiled surfaces. To restore the impregnation, after drying overnight, LOBACARE WPC Refresh (light impregnating effect) or LOBASOL DeckOil (strong impregnating effect) can be applied.

General guidelines

Cleaning of tools: Clean tools and equipment immediately with water.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and relate to Spezial conditions. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice by speaking to the LOBA application engineering department. Observe the floor covering manufacturer's recommendations and the provisions of the current standards. Our liabilities and responsibilities are exclusively in accordance with our Terms and Conditions and are not extended by this information or by our advice. The publishing of a new technical data sheet automatically invalidates the earlier version.

Drying time: The indicated drying times are valid for +20°C and 50% relative humidity, and assume careful, draught-free ventilation of the working area. Lower temperatures, higher relative humidity or poorer ventilation lead to longer drying times. Do not apply any protective coverings or wet clean the surface until full curing is achieved. Product-specific data can be found in the relevant technical information.

The words or symbols denoted by [®] stand for trademark rights that are at least registered and protected in the territory of Germany.

OBA GmbH & Co. KG | Leonberger Str. 56-62 | 71254 Ditzingen | Germany on: +49 7156 357-0 | Fax: +49 7156 357-211 | E-Mail: service@loba.de | www.loba.de