

# TECHNICAL INFORMATION

## DeckFinish Color VARIOUS COLORS



**NEW**

**Reaches the next level: The long-lasting UV light and weather protection for your terrace is here!**

1C water-based finish for exterior wooden surfaces. This outdoor expert sets your terrace perfectly in scene: Whether in trendy gray or noble red-brown - extremely durable DeckFinish Color defies all weather conditions, is slip-resistant and chlorine-resistant. Thanks to its quick and easy application, the robust surface protection also reduces working time.

- Deep protection against UV radiation, frost and moisture
- Chlorine resistant
- Safe, simple processing
- No roughening of the wood
- Short drying time
- Suitable for all types of wood
- Suitable for smooth and grooved planks
- Applicable in a system with LOBADUR DeckPrepare

### Range of use:

Suitable for wooden terraces and decks in outdoor areas.

## Technical Data

### Art.-no.

11842



5 l



4



128

### Solids

37 ±2%

### Storage and transportation

12 months of storage stability. No hazardous material according to ADR. Store and transport between +5 to +25°C. Protect from frost.

### GISCODE


W3+

2004/42/CE

EU limit value for this product (cat. A/i): 140 g/l (2010).  
This product contains max. 74 g/l VOC.



800145  
Light brown



800150  
Dark brown



800099  
Red brown



900148  
Grey

Color samples are not binding

15/12/2020



# TECHNICAL INFORMATION

## DeckFinish Color VARIOUS COLORS



### Application

- Optimum processing conditions at +15°C to +25°C, relative humidity 40% to 75%, material temperature +15°C to +25°C
- Do not apply to surfaces exposed to hot or strong sunlight, as the applied coating may dry too quickly. Do not apply if rain is expected within 3 hours of application.
- If in doubt, create a test area to determine compatibility, adhesion and appearance. The results may vary depending on the type of wood, especially with oily and resinous woods.
- Shake the contents well.
- Transfer material to a LOBATool varnish bucket before applying.
- Avoid drops falling on the surface, smooth out any drops directly with a brush.
- Observe general and, if necessary, product-specific occupational health and safety regulations. Further information can be found in the GISCODE-related operating instructions which are available under [www.wingis-online.de](http://www.wingis-online.de).

### Thinner

The product is ready for use and must not be reduced!

### Application tool/application rate

LOBATool oil brush, soft brush / 100-120ml/m<sup>2</sup>. Actual material consumption may vary depending on the type of wood, wood moisture and the weathering condition of the surface. With strongly weathered surfaces, a significantly higher material consumption must be expected.

### Drying time

- Overworking after 2-3 hours, within 24 hours.
- Light use after drying overnight.
- Full load capacity after 48 hours.

### Pre-Treatment

- Recommended is the pre-treatment with LOBADUR DeckPrepare to optimize the adhesion properties and to counteract wood graying.

15/12/2020



## Application

---

### Preparation:

#### Initial treatment

- Prepare the substrate according to the specifications for "old used decks" or "newly installed decks" in the technical information for the LOBACARE DeckDegrayer product.
- Apply LOBADUR DeckPrepare according to the technical information.
- Drying 1 hour. Wait for complete drying
- Apply LOBADUR DeckFinish Color
- Drying min. 2 hours
- Apply the second layer of LOBADUR DeckFinish Color

#### Follow-up treatment

- Basic cleaning with LOBACARE DeckDegrayer according to technical information about the product
- Apply LOBADUR DeckPrepare according to the technical information.
- Drying 1 hour. Wait for complete drying
- Apply LOBADUR DeckFinish Color

To maintain the visual value of the decking in the long term, we recommend an annual basic cleaning and recoating of the decking.

## General guidelines

---

**Drying time:** The indicated drying times are valid for +20°C and 50% relative humidity, and assume careful, draught-free ventilation of the working area. Lower temperatures, higher relative humidity or poorer ventilation lead to longer drying times. Do not apply any protective coverings or wet clean the surface until full curing is achieved. Product-specific data can be found in the relevant technical information.

**Use of LOBADUR DeckFinish Color without LOBADUR DeckPrepare:** Basically LOBADUR DeckFinish Color can be used without LOBADUR DeckPrepare. The use of LOBADUR DeckPrepare significantly improves the adhesion properties of the finish to the substrate and increases the application safety.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and relate to Spezial conditions. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice by speaking to the LOBA application engineering department. Observe the floor covering manufacturer's recommendations and the provisions of the current standards. Our liabilities and responsibilities are exclusively in accordance with our Terms and Conditions and are not extended by this information or by our advice. The publishing of a new technical data sheet automatically invalidates the earlier version.

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.

