

TECHNICAL INFORMATION

DeckPrepare



NEW

"Anti-Aging" for your sun deck: effective support for the protective final treatment

Primer for wooden decks in outdoor areas. Simple application, double effect: LOBADUR DeckPrepare effectively strengthens protection and adhesion of the subsequent surface finishing with LOBASOL DeckOil / Color or LOBADUR DeckFinish Color. Through powerful stabilization of the wood's own ingredients, LOBADUR DeckPrepare delays the natural graying of the wood.

- Delays the weather-related graying of wood
- Strengthens the protective effect of the subsequent surface refinement
- Improves the adhesion of the subsequent coating to the substrate
- Easy and safe application
- Quick-drying
- Color- and odorless
- Environmentally friendly
- Applicable in a system with LOBADUR DeckFinish Color. Optional application before impregnation with LOBASOL DeckOil / Color

Range of use:

Suitable for wooden decks, patios, garden furniture and other objects made from wood that are used outdoors.

Technical Data

Art.-no.

11841



5 l



4



128

Solids

16.4 ±2%

Viscosity DIN 4

11 ±2s

Storage and transportation

12 months of storage stability. No hazardous material according to ADR. Store and transport between +5 to +25°C. Protect from frost.

GISCODE

W2+

2004/42/CE

EU limit value for this product (cat. A/i): 140 g/l (2010).
This product contains max. 2 g/l VOC.

15/12/2020



TECHNICAL INFORMATION

DeckPrepare



Application

- Optimum processing conditions at +15°C to +25°C, relative humidity 40% to 75%, material temperature +15°C to +25°C
- Do not apply to surfaces exposed to hot or strong sunlight, as the applied coating may dry too quickly. Do not apply if rain is expected within 3 hours of application.
- If in doubt, create a test area to determine compatibility, adhesion and appearance. The results may vary depending on the type of wood, especially with oily and resinous woods.
- Shake the contents well.
- Transfer material to a LOBATool varnish bucket before applying.
- Avoid drops falling on the surface, smooth out any drops directly with a brush.
- Observe general and, if necessary, product-specific occupational health and safety regulations. Further information can be found in the GISCODE-related operating instructions which are available under www.wingis-online.de.

Thinner

The product is ready for use and must not be reduced!

Application tool/application rate

LOBATool oil brush, soft brush / 100-120ml/m². Actual material consumption may vary depending on the type of wood, wood moisture and the weathering condition of the surface. With strongly weathered surfaces, a significantly higher material consumption must be expected.

Drying time

- Drying 1 hour. Wait for complete drying

Systems recommended as a follow-up treatment

- LOBASOL DeckOil & DeckOil Color
- LOBADUR DeckFinish Color

Preparation:

Please refer to the LOBACARE DeckDegrayer technical information for optimal surface pretreatment.

Processing:

- surface must be dry immediately before application
- Apply one layer of LOBADUR DeckPrepare.
- Drying 1 hour. Wait for complete drying
- Then apply LOBASOL DeckOil / Color or LOBADUR DeckFinish Color according to the Technical Information.
- To maintain the visual value of the decking, we recommend an annual basic cleaning and recoating of the decking.

15/12/2020



TECHNICAL INFORMATION

DeckPrepare



General guidelines

Drying time: The indicated drying times are valid for +20°C and 50% relative humidity, and assume careful, draught-free ventilation of the working area. Lower temperatures, higher relative humidity or poorer ventilation lead to longer drying times. Do not apply any protective coverings or wet clean the surface until full curing is achieved. Product-specific data can be found in the relevant technical information.

Use of LOBADUR DeckFinish Color without LOBADUR DeckPrepare: Basically LOBADUR DeckFinish Color can be used without LOBADUR DeckPrepare. The use of LOBADUR DeckPrepare significantly improves the adhesion properties of the finish to the substrate and increases the application safety.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and relate to Spezial conditions. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice by speaking to the LOBA application engineering department. Observe the floor covering manufacturer's recommendations and the provisions of the current standards. Our liabilities and responsibilities are exclusively in accordance with our Terms and Conditions and are not extended by this information or by our advice. The publishing of a new technical data sheet automatically invalidates the earlier version.

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.

15/12/2020

