

LOBADUR 

# EasyFillPro

Water-based binder. For the production of wood filler.

## Emissions



Emicode® EC2,  
low-emission

According to GEV (Community Emission Controlled Flooring  
Adhesives and Construction Products e.V., Düsseldorf)

## Technical evaluation

GISCODE

W2+ (Water-thinnable surface treatment agents, solvent content up to 5%, N-methylpyrrolidone free)

## Glossar

### GEV Emicode

The EMICODE® symbol identifies building materials and products that emit no or very low fugitive emissions into the indoor air. The award is made by GEV, Gemeinschaft Emissionskontrollierter Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V. The GEV was founded in 1997 by industrial companies to promote products that are harmless to health and the environment. External test institutes certified according to ISO 17025 test the emission behaviour of parquet varnishes. In addition, parquet lacquers with a high solvent content are not approved for testing. This means that the needs of users and residents alike are taken into account. Products marked with EMICODE® are checked regularly. [www.emicode.de](http://www.emicode.de)

### GISCODE

The term GISCODE stands for Hazardous Substance Information System Code and was developed by the BG Bau (Employer's Liability Insurance Association for the Construction Industry). It is a labelling system in which products with comparable health hazards are grouped together in product groups. The coding consists of a letter/number combination that uniquely assigns the product to a product group. To obtain specific product information, a product group can be selected on the GISBAU website (= Hazardous Substance Information System of the BG Bau) and detailed hazardous substance information can be found in the appropriate table.

## Notes

### Disclaimer

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and relate to Spezial conditions. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice by speaking to the LOBA application engineering department. Observe the floor covering manufacturer's recommendations and the provisions of the current standards. Our liabilities and responsibilities are exclusively in accordance with our Terms and Conditions and are not extended by this information or by our advice. The publishing of a new technical data sheet automatically invalidates the earlier version.