

# TECHNICAL INFORMATION

# Grundreiniger Spezial



Remover for PVC floors. Dissolves heavy soilings and old care layers.

- Removes old layers of care product
- Removes stubborn dirt
- Optimised for use on PVC
- Protects PVC weld seams

## Range of use:

Suitable for removing old layers of care product on PVC, rubber and asphalt floor coverings. Ideal for PVC and PU sports flooring in the system with LOBACARE® Sportbodenpflege.

## Technical Data

### Art.-no.

10069



10 l



60

pH

9.8

Contents

5 - 15% soap, < 5% non-ionic surfactants, < 5% NTA (nitrilotriacetic acid) and salts thereof, LIMONENE, perfumes

Storage and transportation

36 months of storage stability. Store and transport between +5 to +25°C. Protect from frost. No hazardous material according to ADR.

GISCODE

GG60

## Application

- Shake the contents well.
- Observe the general and, if available, the product-specific health and safety instructions. More specific information relating to GISCODE can be found in the usage instructions, which are available at [www.wingis-online.de](http://www.wingis-online.de).

## Thinner

Water.



# TECHNICAL INFORMATION

# Grundreiniger Spezial



## Application

### Application tool/application rate

LOBATOOL spray can or wiper mop /  $10\text{-}20\text{ml/m}^2 = 50\text{-}100\text{m}^2/\text{l}$  (equivalent to 1-2l per  $100\text{m}^2$  with ready-to-use mixture) depending on the degree of soiling. Cleaning with a single-disc machine and LOBASAND SpecialPad green or a scourer-vacuum machine with suitable pads.

### Application:

Preparation:

Mix stripper in a ratio of 1:4 to 1:6 with water and wet the surface using a LOBATOOL spray can or a wiper mop.

Stripping (cleaning machine) on medium to large areas:

After allowing the product to work for a short while, use a scourer-vacuum machine with suitable abrasive pad discs and vacuum up the resulting dirt immediately.

Stripping (single-disc machine) on small to medium-sized areas:

After allowing the product to work for a short while, clean the surface with a single-disc machine with LOBASAND SpecialPad green underneath. Vacuum up the resulting dirt immediately with a wet vacuum cleaner or use cloths or wiper mops to soak it up.

Stripping (manual) on small areas:

Apply the cleaning fluid and, after a short while, clean the floor manually using a scrubber with a medium-hardness brush. Vacuum up the resulting dirt immediately with a wet vacuum cleaner or use cloths or wiper mops to soak it up.

Initial care:

After every strip, a further initial care step is required with a suitable LOBACARE® care product. The care product must only be applied when the flooring is completely dry.

### Important information

Where there is a heavy build-up of care products, the process may also need to be repeated several times. To finish, wipe over the surface with clean water and neutralise. This can also be done by machine.

## General guidelines

**Cleaning of tools:** Clean tools and equipment immediately with water.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and relate to Spezial conditions. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice by speaking to the LOBA application engineering department. Observe the floor covering manufacturer's recommendations and the provisions of the current standards. Our liabilities and responsibilities are exclusively in accordance with our Terms and Conditions and are not extended by this information or by our advice. The publishing of a new technical data sheet automatically invalidates the earlier version.

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.

