

TECHNICAL INFORMATION

LaminatCleaner



Highly concentrated, pH-neutral cleaner. Quick cleaning, dries without streaks

- Significantly reduces the risk of swollen edges with laminate flooring
- Extremely economical concentrate
- Also suitable for plastic-coated furniture, walls, doors and windows
- Streak-free drying
- Material-protecting and pH-neutral
- Excellent cleaning effect thanks to superb dirt-dissolving power

Range of use:

Suitable for cleaning laminate flooring.

Technical Data

Art.-no.

10443



1 l



12



480

Contents

< 5% non-ionic surfactants, perfumes, BENZYL SALICYLATE, METHYLCHLOROISOTHIAZOLINONE AND METHYLISOTHIAZOLINONE (3:1)

Storage and transportation

36 months of storage stability. No hazardous material according to ADR. Store and transport between +5 to +25°C. Protect from frost.

GISCODE

GU50

Application

- Shake the contents well.
- Observe the general and, if available, the product-specific health and safety instructions. More specific information relating to GISCODE can be found in the usage instructions, which are available at www.wingis-online.de.

Thinner

Water.

Application tool/application rate

LOBATOOL mop. On large areas, use a suitable flat wiper mop or a scourer-vacuum machine. / Depending on the application, add approx. 100 - 200ml to a bucket with 10 l of water, sufficient for 100 m².



TECHNICAL INFORMATION

LaminatCleaner



Application

Application:

Mix the cleaning concentrate with water, using a higher ratio for heavier soiling. Damp-wipe the surface with cleaning solution using a suitable cleaning device.

Using too much water and allowing the product to work for too long can cause swelling of laminate flooring, especially in the joint areas, and must therefore be avoided.

The product is also suitable for use in scourer-vacuum machines.

General guidelines

Cleaning of tools: Clean tools and equipment immediately with water.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and relate to Spezial conditions. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice by speaking to the LOBA application engineering department. Observe the floor covering manufacturer's recommendations and the provisions of the current standards. Our liabilities and responsibilities are exclusively in accordance with our Terms and Conditions and are not extended by this information or by our advice. The publishing of a new technical data sheet automatically invalidates the earlier version.

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.

01/07/2020

