



LOBA GmbH & Co. KG
Leonberger Str. 56-62
71254 Ditzingen
Germany
Tel.: +49 7156 357-0
Fax: +49 7156 357-211
E-Mail: service@loba.de
www.loba.de/en

LOBA is always at your side and ensures your success with both advice and action. Our experienced experts are happy to support you individually with your projects. Our competent technical service team is at your disposal quickly, if you need hands-on assistance on site. You can always rely on us!

Do you have any questions? Do not hesitate to contact us:

LOBASOL®



MarkantColor

Hardwaxoil

Infinite design possibilities with proven properties

New color range – Trendy combinations with MarkantNature

The new color range of the worldwide proven MarkantColor offers a total of 17 colors, classified into three basic colors, seven wood colors and seven trend colors. The colored natural hardwaxoil brings out the natural beauty and grain of the wood. The mixability of all colors and the combination of the light MarkantColor shades with the new MarkantNature offer endless design possibilities.



LOBA – Your partner for surface finishing and care

MarkantColor

New colors – New opportunities

High-quality natural hardwaxoil for coloring parquet and hardwood floors.

Accentuates the natural wood structure and also provides high resistance to dirt and water.

- Smooth and full-bodied look
- Film forming, abrasion resistant
- Water and dirt resistant
- Safe and simple application
- Brings out the natural beauty of wood
- All colors can be mixed with each other
- Combinable with Markant and the new MarkantNature
- Recommended for children's toys according to DIN EN 71-3



Range of use

For coloring parquet and hardwood floors. Suitable for almost all European and exotic wood species according to the LOBA suitability list, see LOBA product catalog and at www.loba.de/en.

Markant

Natural hardwaxoil with a full-bodied look

High-quality film forming oils bring out the natural wood structure and are also highly resistant to dirt and water.

- Smooth and full-bodied appearance
- Film forming, abrasion resistant
- Wasser- und schmutzabweisend
- Safe and simple application
- Ergonomic roll application possible
- Accentuates the natural beauty of wood
- Recommended for children's toys according to DIN EN 71-3
- Anti-slip certified according to BGR 181 and DIN 51130, evaluation class R10

Range of use

Suitable for parquet, wood and cork floors. Suitable for almost all European and exotic wood species according to the LOBA suitability list, see LOBA product catalog and at www.loba.de/en.



MarkantNature

Natural wood look

High-quality natural hardwaxoil. The special formula gives the wood surface an untreated look. The natural color of the wood is still present.

- Non ambering, prevents natural wood yellowing
- Natural look of an untreated floor
- Smooth and full-bodied appearance
- Water and dirt resistant
- Ergonomic roll application
- Safe and simple application
- Recommended for children's toys according to DIN EN 71-3
- Anti-slip certified according to BGR 181 and DIN 51130, evaluation class R10

Range of use

Suitable for all light wood species as well as wood surfaces colored with light MarkantColor colors.



MarkantColor application

- Please note our sanding recommendations for coloration
- Apply MarkantColor carefully in sections with LOBATOOL Trowel
- Immediately equalize with single disc machine and LOBATOOL SpecialPad beige
- Drying overnight, minimum 12 to maximum 24 hours
- Roll Markant (semi-gloss, satin or extramatt) or for light colors MarkantNature with LOBATOOL Oil roller Microfibre 60–80 thin and even
- Walkable after 12 hours
- Usable after 24 hours
- Consumption for trowel application: approx. ca. 20 ml/m²
- Consumption for roller application: approx. ca. 60–100 ml/m²

Art.-no. 10508

Available in 17 colors (750 ml and 100 ml sample cans)

GISCODE Ö60

2nd coat

Roll application
LOBASOL® Markant
(semi-gloss, satin, extramatt)
for all colors

or

Roll application
LOBASOL® MarkantNature
for light colors

1st coat



Please consider the detailed technical information, application advices and set-up recommendations.

Technical Information

