

Printing date 18.01.2019 Version number 5 Revision: 18.01.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: WAKOL PU 272 Kunstrasenklebstoff A
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

WAKOL GmbH Bottenbacher Str. 30 D-66954 Pirmasens info@wakol.com +49 6331 8001 0

· Informing department:

Product safety department. msds@wakol.de

· 1.4 Emergency telephone number:

Emergency CONTACT (24-Hour-Number):

GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



- · Signal word Warning
- · Hazard statements

H226 Flammable liquid and vapour.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P403+P235 Store in a well-ventilated place. Keep cool.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

(Contd. on page 2)



Printing date 18.01.2019 Version number 5 Revision: 18.01.2019

Trade name: WAKOL PU 272 Kunstrasenklebstoff A

· vPvB: Not applicable.

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· **Description**: Adhesive

· Dangerous components:

CAS: 67-64-1 acetone

etone 1.0-<2.5%

Reg.nr.: 01-2119471330-49

· Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation Supply fresh air; consult doctor in case of complaints.
- · After skin contact Clean with water and soap. If possible, also wash with polyethylene glycol 400.
- · After eye contact Rinse opened eye for several minutes under running water.
- · After swallowing Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
- · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 3)



Printing date 18.01.2019 Version number 5 Revision: 18.01.2019

Trade name: WAKOL PU 272 Kunstrasenklebstoff A

(Contd. of page 2)

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

- · Breathing equipment: Use suitable respiratory protective device in case of insufficient ventilation.
- · Recommended filter device for short term use: Combination filter A-P2
- · Protection of hands:



Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

· Material of gloves

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)



Printing date 18.01.2019 Version number 5 Revision: 18.01.2019

Trade name: WAKOL PU 272 Kunstrasenklebstoff A

(Contd. of page 3)

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Pasty
Colour: Beige

Smell: Characteristic
 Odour threshold: Not determined.
 pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined. **Initial boiling point and boiling range:** 421 °C

• Flash point: 44 °C (DIN EN ISO 3679)

Inflammability (solid, gaseous)
 Decomposition temperature:
 Not applicable.

· Self-inflammability: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Critical values for explosion:

Lower: Not determined. Upper: Not determined.

· Steam pressure at 20 °C: 1 hPa

• **Density at 20 °C** 1.85 g/cm³ (EN ISO 2811-1)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

dynamic at 20 °C: 180000 mPas (ISO 2555)

kinematic: Not determined.

· Solvent content:

Organic solvents: 2.0 % Water: 0.0 %

(Contd. on page 5)



Printing date 18.01.2019 Version number 5 Revision: 18.01.2019

Trade name: WAKOL PU 272 Kunstrasenklebstoff A

(Contd. of page 4)

 VOC
 2.0 %

 2.00 %

 VOC (EC)
 0,0 %

Solids content: 98.0 % (DIN EN 827.8.2)

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values that are relevant for classification:

471-34-1 calcium carbonate

Oral LD50 > 5000 mg/kg (rat)

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 6)



Printing date 18.01.2019 Version number 5 Revision: 18.01.2019

Trade name: WAKOL PU 272 Kunstrasenklebstoff A

(Contd. of page 5)

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

· European waste catalogue

08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 04 00 wastes from MFSU of adhesives and sealants (including waterproofing products)

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

· ADR, ADN, IMDG Void · IATA UN1133

· 14.2 UN proper shipping name

· ADR, ADN, IMDG Void

· IATA ADHESIVES

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG

· Class Void

 \cdot IATA



· Class 3 Flammable liquids.

· Label 3

· 14.4 Packing group

· ADR, IMDG Void · IATA III

· 14.5 Environmental hazards:

· Marine pollutant: No

· 14.6 Special precautions for user Not applicable.

· 14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

• Transport/Additional information: Not dangerous according to the above specifications.

(Contd. on page 7)



Printing date 18.01.2019 Version number 5 Revision: 18.01.2019

Trade name: WAKOL PU 272 Kunstrasenklebstoff A

(Contd. of page 6)

 $\cdot ADR$

• Remarks: Is not subject to the regulations of ADR for packings up to

450 l (see ADR 2.2.3.1.5)

· IMDG

• Remarks: Is not subject to the regulations for placards, labeling and

examination after the IMDG code for packings up to 30 l

transport in accordance with IMDG Code 2.3.2.5

· UN "Model Regulation": Void

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations
- · VOC:
- · VOC (EU) 37.0 g/l
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.

GB ·



Printing date 18.01.2019 Version number 6 Revision: 18.01.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: WAKOL PU 272 Kunstrasenklebstoff B
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Hardening agent/ Curing agent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

WAKOL GmbH Bottenbacher Str. 30 D-66954 Pirmasens info@wakol.com

+49 6331 8001 0

· Informing department:

Product safety department. msds@wakol.de

· 1.4 Emergency telephone number:

Emergency CONTACT (24-Hour-Number):

GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





J11307 G11300

· Signal word Danger

(Contd. on page 2)



Printing date 18.01.2019 Version number 6 Revision: 18.01.2019

Trade name: WAKOL PU 272 Kunstrasenklebstoff B

(Contd. of page 1)

· Hazard-determining components of labelling:

diphenylmethanediisocyanate,isomeres and homologues

· Hazard statements

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

· Additional information:

Contains isocyanates. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Adhesive
- Dangerous components:

CAS: 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues

50-100%

EC number: 618-498-9 Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335

· Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation Supply fresh air; consult doctor in case of complaints.
- · After skin contact Clean with water and soap. If possible, also wash with polyethylene glycol 400.
- · After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

 (Contd. on page 3)

- GB



Printing date 18.01.2019 Version number 6 Revision: 18.01.2019

Trade name: WAKOL PU 272 Kunstrasenklebstoff B

(Contd. of page 2)

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Hydrogen cyanide (HCN)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

- 5.3 Advice for firefighters
- · Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Prevent formation of aerosols.
- Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- ·Storage
- Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

(Contd. on page 4)



Printing date 18.01.2019 Version number 6 Revision: 18.01.2019

Trade name: WAKOL PU 272 Kunstrasenklebstoff B

(Contd. of page 3)

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- · Breathing equipment: Use suitable respiratory protective device in case of insufficient ventilation.
- · Recommended filter device for short term use: Combination filter A-P2
- · Protection of hands:



Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eve protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing

- GB



Printing date 18.01.2019 Version number 6 Revision: 18.01.2019

Trade name: WAKOL PU 272 Kunstrasenklebstoff B

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid
Colour: Green

Smell: Characteristic
Odour threshold: Not determined.

pH-value: Not determined.

· Change in condition

Melting point/freezing point: 10 °C Initial boiling point and boiling range: 201 °C

· Flash point: >200 °C

· Inflammability (solid, gaseous) Not applicable.

• Ignition temperature: >600 °C

· **Decomposition temperature:** Not determined.

· Self-inflammability: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Critical values for explosion:

Lower: Not determined.

Upper: Not determined.

Steam pressure at 20 °C: <0.00001 hPa

• **Density at 20 °C** 1.23 g/cm³ (EN ISO 2811-1)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

dynamic at 20 °C: 90 mPas (ISO 2555) kinematic: Not determined.

· Solvent content:

 Organic solvents:
 0.0 %

 Water:
 0.0 %

 VOC
 0.0 %

 0.00 %
 0.00 %

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

(Contd. on page 6)



Printing date 18.01.2019 Version number 6 Revision: 18.01.2019

Trade name: WAKOL PU 272 Kunstrasenklebstoff B

(Contd. of page 5)

- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Reacts with alcohols, amines, aqueous acids and alkalis.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if inhaled.

· LD/LC50 values that are relevant for classification:

9016-87-9 diphenylmethanediisocyanate,isomeres and homologues

Oral LD50 >10000 mg/kg (rat)

Dermal LD50 >9400 mg/kg (rabbit)

Inhalative LC50/4h 11 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eve damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity

Suspected of causing cancer.

- $\cdot \textit{Reproductive toxicity } \textit{Based on available data, the classification criteria are not met.}$
- · STOT-single exposure

May cause respiratory irritation.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

9016-87-9 diphenylmethanediisocyanate,isomeres and homologues

LC50/96h > 1.000 mg/l (Danio rerio)

LC0/96h >1000 mg/l (Brachydanio rerio)

EC50/24h > 100 mg/l (bacteriums)

EC50/48h > 1.000 mg/l (Daphnia magna)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

(Contd. on page 7)



Printing date 18.01.2019 Version number 6 Revision: 18.01.2019

Trade name: WAKOL PU 272 Kunstrasenklebstoff B

(Contd. of page 6)

- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

· European waste catalogue

08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 05 00 wastes not otherwise specified in 08

08 05 01* waste isocyanates

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

· ADR, ADN, IMDG, IATA Void

· 14.2 UN proper shipping name

· ADR, ADN, IMDG, IATA Void

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG, IATA

· Class Void

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Not applicable.

· 14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

• Transport/Additional information: Not dangerous according to the above specifications.

· UN "Model Regulation": Void

- GB



Printing date 18.01.2019 Version number 6 Revision: 18.01.2019

Trade name: WAKOL PU 272 Kunstrasenklebstoff B

(Contd. of page 7)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations
- · Other regulations, limitations and prohibitive regulations
- · GEV-Guidline/EMICODE:

EC 1 plus R, "very low emission"

(as ready-for-use mixture with component A)

- · VOC:
- **VOC (EU)** 0,0 g/l
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2